


**Declaration of Performance**

Annex III of regulation (EU) Nr. 305/2011



**Intectin® Plus (IPUP01)**

No. G4B-Intectin-2023-V.05



1.	<b>Unique identification code of the product type</b>	<b>Intectin® Plus</b>
2.	<b>Intended use/es:</b>	<b>concrete injection for ductile filling of cracks, voids and interstices</b> U (D1) W(2) (1/2/3) (5/30)
3.	<b>Manufacturer:</b>	<b>MAX FRANK GmbH &amp; Co. KG</b> Mitterweg 1, 94339 Leiblfing, Germany
4.	<b>Authorised representative:</b>	not relevant (see 3.)
5.	<b>System/s of AVCP:</b>	<b>System 2+</b> (for uses in buildings and civil engineering works)
6a.	<b>Harmonised standard:</b>	<b>MPA Braunschweig</b> 0761-CPR-1230
6b.	<b>European Assessment Document:</b>	not applicable

7. Declared performance/s:

Basic Characteristics	Performance	Harmonized technical specification
Adhesion	0,6 N/mm <sup>2</sup>	EN 1504-5: 2004
Elongation	> 10%	
Watertightness	D1	
Glass transition temperature	-40°C	
Injectability into dry medium	Injectability class 0.2 and 0.3	
Injectability into non-dry medium	Injectability class 0.2 and 0.3	
Durability (Compatibility with concrete)	No failure in compression, lost deformation work < 20 %.	
Corrosion behaviour	It is assumed that no corrosive effects are present.	
Release of dangerous substances	NPD	

8. Appropriate Technical Documentation and/or Specific Technical Documentation: ---

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by



Dipl.-Ing. B.Sc. Moritz Michel  
Head of Technology and Innovation

Leiblfing, 04.09.2023