

## Declaration of Performance

Annex III of regulation (EU) Nr. 305/2011



## Zemseal® Flex Paste

### G4C-FlexPaste-2021\_V.01

<b>1. Product Type:</b> Unique identification code of the product type	<b>Zemseal® Flex Paste</b>
<b>2. Type:</b> Batch or serial number or any other element allowing identification of the construction product as required under Article 11(4)	<b>Batch number:</b> Refer to product label
<b>3. Intended Use:</b> Or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer	<b>Plastic-modified bitumen thick coating (PMB) for waterproofing building components in contact with the ground</b>
<b>4. Name, registered trade name:</b> Or registered trademark and contact address of the manufacturer as required under Article 11(5)	<b>Zemseal® Flex Paste</b> MAX FRANK GmbH & Co. KG, Mitterweg 1, 94339 Leiblfing, Germany
<b>5. Contact address:</b> Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2)	Not relevant (see 4)
<b>6. AVCP:</b> System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V	System 3 System 3 for fire resistance
<b>7. Notified body (hEN):</b> In case of the declaration of performance (DoP) concerning a construction product covered by a harmonized standard	Materialprüfungsamt Nordrhein-Westfalen, identification number 0432
<b>8. Notified body (ETA:)</b> In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued	not relevant

**9. Declared Performance:**

Harmonized technical specification EN 15814:2012 + A1:2014

Basic Characteristics	Declared Performance
Water tightness	Class W2A
Crack bridging capability	Class CB2
Resistance to water	No discoloration of the water, No detachment from the liner
Flexibility at low temperatures	No cracks
Dimensional stability at high temperatures	No slipping and running
Fire resistance	Class E
Compressive strength	Class C2A
Dangerous substances	NPD
Durability of water tightness and fire behavior	fulfilled

**10. Declaration:**

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by



.....  
Dipl.-Ing. B.Sc. Moritz Michel  
Head of Technology and Innovation

Leiblfing, 18th March 2021